

# STANDARD HORIZON

*Nothing takes to water like Standard Horizon*

## 2013 Marine Communications Product Catalog





# THE LEADER IN MARINE COMMUNICATIONS

## Our mission:

Our mission is quite simple, "Produce the finest Marine Communications in the market to meet the needs of Boaters everywhere". For more than 50 years, Standard Horizon has built and delivered the finest radios and GPS chartplotters on the market and that's why we can say...

*"Nothing takes to water like Standard Horizon".*

 SUBMERSIBLE	 SUBMERSIBLE	 FLOATING	 RADAR	 STROBE LIGHT	 LOUD AUDIO 700mW	 LOUD AUDIO	 RUBBER GRIP
 NOAA WEATHER CHANNELS / ALERT	 CLASS D	 DSC DISTRESS and POS Polling	 LAND MOBILE CHANNELS	 16 / 9	 AVAILABLE IN BLACK OR WHITE	 LOUD HAILER	 6W Transmit Power <small>*5 W for Australia Version</small>
 LARGE DISPLAY	 LUMINESCENT Gasket	 E 2 O Easy To Operate	 OPTIONAL MIC / HEADSET	 SECOND STATION	 TONE CONTROL	 GPS COMPASS	 WAYPOINT NAV
 FISH FINDER	 80 dB RECEIVER	 CUSTOMIZABLE SCREENS	 PICTURE IN PICTURE	 GPS	 High Capacity Li-ion Battery Included	 3.7V Battery technology	 AC and DC Charger Included
 USB Charger Included	 WATER PROOF 3 YEAR GUARANTEE STANDARD HORIZON						



# A FAMILY OF MARINE COMMUNICATIONS

A WIDE RANGE OF PRODUCTS TO SUIT YOUR NEEDS

## HANDHELD VHF RADIOS

page 3



## FLOATING HANDHELD VHF RADIOS

page 4



## FIXED MOUNT VHF RADIOS / LOUDHAILER

page 7



## MULTIMEDIA CHARTPLOTTERS

page 11



## GPS CHARTPLOTTERS

page 12



## GPS CHARTPLOTTER / FISH FINDERS




# HANDHELD VHF RADIOS

DESIGNED SPECIFICALLY FOR USE IN HARSH MARINE ENVIRONMENTS



## HX400

COMMERCIAL VHF WITH LMR CHANNELS



Features:

- Submersible IPX8 (5 Ft or 1.5 m for 30 minutes)
- Selectable 5 or 1 Watt transmit power output
- Built-in True Noise Cancelling Microphone
- 40 Programmable Land Mobile Channels 134 MHz to 174 MHz with CTCSS and DCS signaling
- Programmable channel names
- NOAA Weather channels and Weather Alert
- Low battery indicator
- Built-in Voice Scrambler for private communications
- Optional speaker microphones and headsets available
- Supplied with 2400 mAh Li-Ion battery, AC and DC rapid chargers and cradle
- Programmable Scan, Priority Scan and Dual Watch
- Preset key used to recall up to 10 favorite channels



## HX370S

COMMERCIAL VHF WITH LMR CHANNELS



Features:

- 40 Programmable Land Mobile Channels with CTCSS and DCS signaling
- Speaker microphone jack
- Selectable 5/1 W transmit power output
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- Supplied with 1400 mAh Ni-MH battery, alkaline battery tray, AC and DC chargers and cradle
- Programmable Scan, Priority Scan and Dual Watch
- SOS Strobe Light
- Heavy duty die-cast frame
- Voice Scrambler capable



## HX280S

BEST OF THE BASICS



Features:

- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- More than 13 hours of battery life
- Selectable 5 and 1 Watt transmit power output
- Supplied with 1650 mAh Lithium-ion battery, AC and DC chargers and charging cradle
- Huge channel display
- Programmable Scan, Priority Scan and Dual Watch
- NOAA Weather channels and Weather Alert
- Low battery indicator
- Preset key used to recall up to 10 favorite channels



# COMMERCIAL GRADE MARINE HANDHELD VHF RADIOS

BUILT BY PROFESSIONALS FOR PROFESSIONALS

## HX400IS

INTRINSICALLY SAFE



All the great features of the HX400IS, tested and certified Intrinsically Safe.

INTRINSICALLY SAFE INFORMATION:

The HX400IS, FNB-115LIIS Li-ION battery pack and optional MH-66d4s and CMP460

speaker microphones meet the ANSI/UL 913-5th Ed. Requirements for: Class I:

Flammable Gases, Vapors, or Liquids Div. 1

Group A (Acetylene) Group B (Hydrogen)

Group C (Ethylene) Group D (Propane)

Class II: Combustible Dusts Div. 1

Group E (Metals) Group F (Coal) Group G (Grain)

Class III: Ignitable Fibers and flyings



## HX370SAS

INTRINSICALLY SAFE



All the great features of the HX370S in an intrinsically safe housing.

INTRINSICALLY SAFE INFORMATION:

The HX370SAS, FNB-V57AIS 1250 mAh Ni-MH battery pack, optional CMP460 speaker microphone and FVP-31 voice scrambler meet the ANSI/UL 913-5th Ed.

Requirements for: Class I:

Flammable Gases, Vapors, or Liquids Div. 1

Group A (Acetylene) Group B (Hydrogen)

Group C (Ethylene) Group D (Propane)

Class II: Combustible Dusts Div. 1

Group E (Metals) Group F (Coal) Group G (Grain)

Class III: Ignitable Fibers and flyings





# FLOATING HANDHELD VHF RADIOS

LEADING THE INDUSTRY WITH THE FIRST FLOATING VHF WITH GPS



## HX851



FLOATING 6 WATT HANDHELD VHF WITH GPS



### Features:

- Floating
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- Built-in 12 Channel GPS Receiver
- Luminescent Glow in the Dark gasket
- Waypoint entry (200 waypoints) and navigation
- Navigate to DSC Position Request call
- 6 Watt Transmit power
- DSC functions include: Distress call with position, All ships, Urgency, Safety, Individual call, Position Request, Position Report and Group call
- Programmable Scan, Priority Scan and Dual Watch
- Battery life indication
- Preset key used to recall up to 10 favorite channels
- Water activated SOS Strobe light
- NOAA Weather channels and Weather Alert
- 700 mW Loud speaker audio
- Selectable Power Output 6/5/2.5/1 Watt
- Supplied with 1380 mAh Li-Ion battery, AC and DC chargers and cradle



## HX300

COMPACT FLOATING HANDHELD VHF



### Features:

- Floating
- Submersible IPX8 (5 Ft or 1.5 m for 30 minutes)
- 5 Watt Transmit power
- Unique USB charging system
- E20 (Easy To Operate) menu system
- Volume & Squelch indication display
- Water enabled light, when dropped into the water
- Preset key (Maximum 10 channels)
- Preset channel scan function
- 600 mW loud internal speaker audio
- NOAA Weather Channels
- Programmable Scan, Priority Scan, Dual Watch and Triple Watch
- Supplied with 1560 mAh 3.7V Li-Ion battery, AC USB type charger and cable



## HX290

FLOATING 5 WATT HANDHELD VHF



### Features:

- Floating
- Submersible IPX8 (5 Ft or 1.5 m for 30 minutes)
- Glow-In-The-Dark strip
- Selectable 5 and 1 Watt transmit power output
- Huge channel display
- Optional Speaker microphone or Headset capable
- Programmable Scan, Priority Scan and Dual Watch
- NOAA Weather channels and Weather Alert
- Key lock
- Low battery indicator
- Preset key used to recall up to 10 favorite channels
- Supplied with 1170 mAh Li-Ion battery, AC and DC chargers and cradle



## HX100

NEW FOR 2013

Floating 2.5 Watt Handheld VHF Twin-Pack



### Features:

- Floating
- Two Transceivers included
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- Slim, form fitting case design
- More than 7.5 hours of battery life
- E20 (Easy To Operate) menu system
- Selectable 2.5 and 1 Watt transmit power output
- Large channel display
- 500 mW loud internal speaker audio
- All USA, International and Canadian Marine Channels
- Programmable Scan, Priority Scan and Dual Watch
- NOAA Weather channels and Weather Alert
- Squelch level on display
- Battery life indicator
- Key lock
- Supplied with a 700 mAh Ni-MH battery, 110 VAC and twin charging cradle

Twin Pack



## HX150

NEW FOR 2013

Floating 5 Watt Handheld VHF



### Features:

- Floating
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- Slim, form fitting case design
- 10 hours of battery life
- E20 (Easy To Operate) menu system
- Selectable 5 and 1 Watt transmit power output
- Large channel display
- 500 mW loud internal speaker audio
- All USA, International and Canadian Marine Channels
- Programmable Scan, Priority Scan and Dual Watch
- NOAA Weather channels and Weather Alert
- Squelch level on display
- Battery life indicator
- Key lock
- Supplied with a 1030 mAh Li-Ion battery, 110 VAC and charging cradle



# HANDHELD VHF ACCESSORIES

THE ACCESSORIES YOU NEED!

## FNB-121LI

1380 mAh Li-Ion battery



## FNB-115LI

2400 mAh Li-Ion battery



## MH-73A4B

Speaker Microphone



## PA-48B

110VAC Wall Charger



## VC-24

Headset with VOX



## FBA-38

Alkaline battery tray  
(AAA type cell x 5)



## MH-6604B

Speaker Microphone



## E-DC-19A

12VDC cigarette lighter charger




## CD-56

Twin Charging cradle



## FVP-31

Scrambler board



## HANDHELD VHF ACCESSORIES

MODEL	Description	HX851	HX400	HX400IS*	HX370S	HX370SAS*	HX300	HX290	HX280S	HX150	HX100
CAT460	VHF marine antenna	○	○	○	○	○	○	○	○		
CD-26	Charging cradle used with PA-48B/C				○	○					
CD-38	NMEA Charging cradle used with PA-48B/C	○									
CD-46	Charging cradle used with PA-48B/C								○		
CD-50	3-hour Charging cradle used with PA-45B/C		○	○							
CD-52	Charging cradle used with PA-48B/C							○			
CD-56	Twin Charging cradle										○
CD-57	Charging cradle									○	
CLIP-14	Belt clip				○	○					
CLIP-19	Belt clip	○									
CLIP-22	Belt clip		○	○			○	○			
CLIP-24	Belt clip									○	○
CMP460	Submersible speaker microphone (IS rated)*	○	○	○	○	○		○			
E-DC-6	12VDC cable	○			○	○		○	○	○	○
E-DC-19A	DC cable with cigarette lighter plug	○			○	○		○	○	○	○
E-DC-30	DC cable with cigarette lighter plug used with CD-50 only		○	○							
FBA-38	Alkaline battery tray	○									
FBA-40	Alkaline battery tray								○		
FBA-42	Alkaline battery tray		○					○			
FBA-44	Alkaline battery tray						○				
FNB-V57AIS	Intrinsically safe 1250 mAh Ni-MH battery					○					
FNB-83	1400 mAh Ni-MH battery				○						
FNB-V105LI	1650 mAh Lithium-ion battery								○		
FNB-V110LI	1170 mAh Lithium-ion battery							○			
FNB-115LI	2400 mAh Lithium-ion battery		○								
FNB-115LIIS	Intrinsically safe 2400 mAh Lithium-ion battery*			○							
FNB-121LI	1380 mAh Lithium-ion battery	○									
FNB-122LI	1560 mAh Lithium-ion battery						○				
FNB-124LI	1030 mAh Lithium-ion battery									○	
FNB-125	700 mAh Ni-MH battery										○
FVP-31	Scrambler 4 code				○	○					
LCC-370	Leather case				○	○					
LCC-530S	Leather case		○	○							
MCC-270	Nylon radio case				○	○					
MH-57A4B	Mini speaker microphone with earphone jack	○	○		○			○			
MH-66D4B	Submersible speaker microphone	○	○	○	○	○		○			
MH-73A4B	Submersible speaker microphone	○	○	○	○			○			
PA-45B	110AC 3-hour charger used with CD-50		○	○							
PA-45C	240AC 3-hour charger used with CD-50		○	○							
PA-48B	110VAC charger used with CD-26/38/39/46/52/56/57	○			○	○		○	○	○	○
PA-48C	240VAC charger used with CD-26/38/39/46/52/56/57	○			○	○		○	○	○	○
PA-54B	110VAC USB Wall Charger						○				
PA-54C	240VAC USB Wall Charger						○				
VAC-370B	110VAC rapid charger				○	○					
VAC-370C	240VAC rapid charger				○	○					
VC-24	VOX headset	○	○		○			○			
VC-27	Earpiece/microphone	○	○		○			○			

\*Intrinsically Safe Version



# PRODUCT SPECIFICATIONS

THE QUALITY YOU CAN COUNT ON

SUBMERSIBLE	HX400	HX400IS	HX370S/HX370SAS	HX280S
				
GENERAL				
Battery type / Capacity	Li-ion 2400 mAh	Li-ion 2400 mAh	Ni-MH 1400 mAh / Ni-MH 1250 mAh	Li-ion 1650 mAh
Input Voltage	7.4 V DC	7.4 V DC	7.2 V DC	7.4 V DC
Current Drain	Standby: 50 mA	Standby: 50 mA	Standby: 40 mA	Standby: 50 mA
	Receive: 320 mA (MAX AF Output)	Receive: 320 mA (MAX AF Output)	Receive: 200 mA (MAX AF Output)	Receive: 320 mA (MAX AF Output)
	Transmit: 1.6 A / 0.8A (5 W / 1 W)	Transmit: 1.6 A / 0.8A (5 W / 1 W)	Transmit: 1.4 A / 0.9 A / 0.5 A (5 W / 2.5 W / 1 W)	Transmit: 1.6 A / 0.7 A (5 W / 1 W)
Overall Dimensions	2.24"W x 5.24"H x 1.57"D (57W x 133H x 40D mm)	2.24"W x 5.24"H x 1.57"D (57W x 133H x 40D mm)	2.3"W x 4.7"H x 1.2"D (58W x 120H x 30.5D mm)	2.2"W x 5.3"H x 1.1"D (56W x 133H x 27.5D mm)
Weight	12.3 oz (350 g) (w/FNB-115LI, Belt Clip & Antenna)	12.3 oz (350 g) (w/FNB-115LI, Belt Clip & Antenna)	13.4 oz (380 g)(w/FNB-83, Belt Clip & Antenna)	10.9 oz (310 g)(w/FNB-V105LI, Belt Clip & Antenna)
TRANSMITTER				
RF Output	5 W / 1 W (@7.4 V)	5 W / 1 W (@7.4 V)	5 W / 2.5 W / 1 W (@7.2 V)	5 W / 1 W (@7.4 V)
Conducted Spurious Emissions	-75 dBc Typical	-75 dBc Typical	At least -73 dBc Typical	-75 dBc Typical
Frequency Stability	±2.5 ppm (-22° F to +140° F)	±2.5 ppm (-22° F to +140° F)	±2.5 ppm (-22° F to +140° F)	±5 ppm (-4° F to +140° F)
FM Hum and Noise	40 dB	40 dB	40 dB	40 dB
RECEIVER				
Sensitivity (12 dB SINAD)	0.25 µV	0.25 µV	0.25 µV	0.25 µV
Selectivity	70 dB(25 kHz) / 60 dB(12.5 kHz)	70 dB(25 kHz) / 60 dB(12.5 kHz)	70 dB	70 dB
Audio Output	700 mW	700 mW	600 mW	700 mW
NMEA In/Out	-	-	-	-

FLOATING	HX851	HX300	HX290	HX150/HX100
				
GENERAL				
Battery type / Capacity	Li-ion 1380 mAh	Li-ion 1560 mAh	Li-ion 1170 mAh	Li-ion 1030 mAh / Ni-MH 700 mAh
Input Voltage	7.4 V DC	3.7 V DC	7.4 V DC	4.8 V DC / 7.4 V DC
Current Drain	Standby, GPS On: 100 mA	Standby: 20 mA	Standby: 50 mA	Standby: 15 mA
	Standby, GPS Off: 60 mA			
	Receive: 330 mA (MAX AF Output)	Receive: 330 mA (Typical at MAX AF Output)	Receive: 320 mA (MAX AF Output)	Receive: 300 mA / 300 mA (MAX AF Output)
Transmit: 1.6 A / 1.5 A / 1.0 A / 0.7 A (6 W / 5 W / 2.5 W / 1 W)	Transmit: 2.3 A / 0.9 A (5 W / 1 W)	Transmit: 1.6 A / 0.7 A (5 W / 1 W)	Transmit: 1.5 A / 0.7 A HX100: 1.1 A / 0.8 A (5 W / 1 W) (2.5 W / 1 W)	
Overall Dimensions	2.5"W x 5.6"H x 1.8"D (62.5W x 141.5H x 45D mm)	2.32" x 5.04" x 1.3" (59W x 128H x 33D mm)	2.2"W x 5.2"H x 1.7"D (57W x 133H x 44D mm)	2.4"W x 5.3"H x 1.5"D (62W x 135H x 38.5D mm)
Weight	11.8 oz (335 g) (w/FNB-V121LI, Belt Clip & Antenna)	8.4 oz (240 g) (w/FNB-122LI, Belt Clip & Antenna)	10.9 oz (310 g) (w/FNB-110LI, Belt Clip & Antenna)	HX150: 8.3 oz (235 g) (w/FNB-124LI, Belt Clip & Antenna) HX100: 8.6 oz (245 g) (w/FNB-125, Belt Clip & Antenna)
TRANSMITTER				
RF Output	6 W / 5 W / 2.5 W / 1 W (@7.4 V)	5 W / 1 W (@3.7 V)	5 W / 1 W (@7.4 V)	HX150: 5 W / 1 W (@7.4 V) HX100: 2.5 W / 1 W (@4.8 V)
Conducted Spurious Emissions	-75 dBc Typical	-75 dBc Typical	-75 dBc Typical	-75 dBc Typical
Frequency Stability	±10 ppm (-4° F to +140° F)	±5 ppm (-4° F to +140° F)	±10 ppm (-4° F to +140° F)	±5 ppm (-4° F to +140° F)
FM Hum and Noise	40 dB	40 dB	40 dB	40 dB
RECEIVER				
Sensitivity (12 dB SINAD)	0.25 µV	0.25 µV	0.25 µV	0.3 µV
Selectivity	70 dB Typical	70 dB Typical	70 dB Typical	65 dB Typical
Audio Output	700 mW	600 mW	700 mW	500 mW
DSC Format	ITU-R M493-13	-	-	-
NMEA In/Out	Output: GLL, GGA and RMC	-	-	-
	Input: GLL, GGA, GSA, GSV, DSC, DSE and RMC	-	-	-
	HX851 GPS Specifications			
Channels	12 channels			
Sensitivity	Less than -130 dBm			
Time to First Fix	1 min Typical (@Cold Start)			
	40 sec Typical (@Warm Start)			
Geodetic Datum	WGS84			

Standard Horizon reserves the right to make changes and enhancements to products at our discretion. Current specifications are therefore subject to change without notice.



# FIXED MOUNT VHF RADIOS

POWER, PERFORMANCE, RELIABILITY



**BUILT-IN AIS**

## GX2150

**MATRIX AIS+ TRUCLASS D**

First Fixed Mount VHF  
With Built-In AIS receiver  
30 W PA/FOG-RAM3 COMPATIBLE



Also available in white



### Features :

- Integrated dual channel AIS (Automatic Identification System) receiver
- 4800 or 38400 NMEA baud rate selection, for plotters with 1 NMEA port
- AIS target display: MMSI, Call Sign, Ship Name, BRG, DST, SOG and COG
- Meets ITU-RM493-13 Class D (Digital Selective Call)
- Call an AIS Class A or B AIS Ship with DSC\*
- Programmable CPA or TCPA collision avoidance alarms\*
- Submersible IPX7 (1 m/3.3 Ft for 30 minutes)
- 80dB Commercial grade receiver
- DSC position request and report functions when connected to a compatible GPS chart plotter
- 30 Watt PA/Loud Hailer with preprogrammed fog signals and listen back
- ClearVoice noise canceling speaker microphone with channel selection and 16/9 key
- GPS Compass, Waypoint and GPS status pages\*
- Navigation (LAT/LON, Time, SOG and COG) information shown on display\*
- Enter, Save and Navigate to waypoints with Compass page\*
- Versatile user-programmable scanning, priority scan and Dual Watch
- Oversized rotary channel knob with push to enter, backlit display and keys
- Optional connection for RAM3 second station remote microphone with AIS display
- Local/Distance attenuator
- Supplied with HC2000 Dust Cover

\*When connected to a GPS



## GX2000

**MATRIX TRUCLASS D**

FIXED MOUNT DSC VHF WITH AIS INPUT,  
30 W PA/FOG-RAM3 COMPATIBLE



### Features :

- AIS (Automatic Identification System) receiver or transponder connection
- AIS target display: MMSI, Call Sign, Ship Name, BRG, DST, SOG and COG\*1,2
- Contact AIS Ship with DSC\*1,2
- CPA (Closest Point of Approach) Alarm\*1,2

- 80dB Commercial grade receiver
- Class D DSC (Digital Selective Calling) with Individual, Group, All ship, Position Report, Request and Distress
- Meets ITU-RM493-13 Class D (Digital Selective Call)
- Local/Distance attenuator
- Enter, Save and Navigate to waypoints with Compass page\*2
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- ClearVoice noise canceling speaker microphone with channel selection and 16/9 key
- Oversized rotary channel knob with push to enter, backlit display and keys
- 30 Watt PA/Loud Hailer with pre-programmed fog signals
- Capable of connecting an optional RAM3 second station remote microphone
- Able to control all radio, DSC, Hailer and AIS (when connected) functions remotely with optional RAM3
- Intercom between radio and RAM3
- Versatile user-programmable scanning, priority scan and Dual Watch
- Navigation (LAT/LON, SOG and COG) information shown on display\*2
- Supplied with HC2000 Dust Cover

\*1 when connected to an optional AIS receiver or transponder

\*2 when connected to an optional GPS




## GX1700

**EXPLORER GPS TRUCLASS D**

Ultra thin and compact  
First Fixed Mount VHF with BUILT-IN GPS!



Also available in black



### Features:

- Fixed Mount VHF with BUILT-IN 12 channel GPS
- Ultra thin and compact rear case design (3.5" depth)
- Meets ITU-RM493-13 Class D (Digital Selective Call)
- Automatically poll the GPS position of up to 4 ships using DSC
- Enter, Save, and Navigation to Waypoint with Compass page
- GPS Compass display
- Navigation (LAT/LON, SOG, and COG) information shown on display
- Submersible IPX8 (5 Ft or 1.5 m for 30 minutes)
- Noise canceling microphone with channel UP/DOWN, 16/9 and H/L keys
- NOAA weather channel selection with alert
- Programmable Scan, Priority Scan, and Dual Watch
- Preset key (Maximum 10 channels)
- GPS repeating of position, SOG, COG and time
- Customizable channel names
- NMEA Input and Output GPS information when connected to another NMEA device
- Programmable soft keys
- Capable of connecting to a Second Station RAM3 Remote Access Microphone
- Die-cast chassis



# FIXED MOUNT VHF RADIOS

POWER, PERFORMANCE, RELIABILITY



Also available in black

## GX1600

**EXPLORER** *TRUCLASSO*

ULTRA COMPACT FIXED MOUNT DSC  
VHF-RAM3 COMPATIBLE



### Features :

- Ultra thin and compact rear case design (3.5" depth)
- DSC test call
- Meets ITU-RM493-13 Class D (Digital Selective Call)
- Automatically poll the GPS position of up to 4 ships using DSC
- Enter, Save, and Navigation to waypoint with Compass page\*
- GPS Compass display
- Navigation (LAT/LON, SOG, and COG) information shown on display\*
- Submersible IPX8 (5 Ft or 1.5 m for 30 minutes)
- Noise canceling microphone with channel UP/DOWN, 16/9 and H/L keys
- NOAA weather channel selection with alert
- Programmable Scan, Priority Scan, and Dual Watch
- NMEA Input and Output
- Programmable soft keys
- Capable of connecting to a Second Station RAM3 Remote Access Microphone
- Die-cast chassis
- \* when connected to optional GPS



Also available in black

## GX1200

NEW FOR 2013

**ECLIPSE DSC+** *TRUCLASSO*

Fixed Mount Class D DSC VHF



### Features:

- Affordable Ultra Compact Class D Fixed Mount VHF radio
- Replaces older Eclipse+, Eclipse DSC and Eclipse DSC+ Models
- Full dot matrix display
- User programmable soft keys for easy menu operation
- 16/9, H/L and channel up/down keys on the mic
- DSC Distress, Individual, Group, All Ships, Position Request, Position Request and DSC Test Call
- Auto DSC channel change selection
- Submersible IPX7 (3.3 Ft or 1 m for 30 minutes)
- GPS position and Time shown on display\*
- Programmable Scan, Priority Scan, and Dual Watch
- NOAA Weather Channels with Alert
- All USA, International and Canadian Marine Channels
- NMEA 0183 Input and Output
- Meets ITU-RM493-13 Class D (Digital Selective Call)
- Overall Dimension: 2.4" H x 6.1" W x 6.7" D
- Flush Mount Cutout: 2.0" H x 5.2" W
- \* when connected to optional GPS

# COMMERCIAL GRADE MARINE VHF'S AND LOUD HAILER

BUILT BY PROFESSIONALS FOR PROFESSIONALS



## GX5500S

**QUANTUM** *TRUCLASSO*

FIXED MOUNT DSC VHF  
WITH ALPHANUMERIC KEYPAD,  
30 W PA/FOG-RAM3 COMPATIBLE



### Features :

- Meets ITU-RM493-13 Class D (Digital Selective Call)
- 80 dB Commercial grade receiver
- Bluetooth® capable headset (Optional BTK-2 Kit)
- Direct keypad entry of channels
- 30 Watt PA, FOG, Bells and Whistles with listen back
- Bass and Treble Audio Tone Control
- Noise canceling speaker microphone
- Large rotary knobs, and oversized display
- Second station capable with RAM3 or VH-310
- Front Panel microphone can be removed to rear panel and extended to 20 feet using MEK-4
- Features a large alpha numeric keypad



## VLH-3000

30 W DUAL ZONE LOUD HAILER

### Features :

- 30 Watt PA output
- Forward and aft dual zone hailer with listen back
- Bells & whistles and 4 fog signals
- Noise canceling microphone
- Easy push button control
- Loud internal speaker audio
- Dual zone intercom capability with connection of up to 2 optional MLS-300i intercom speakers



# FIXED MOUNT VHF ACCESSORIES

GET THE JOB DONE RIGHT, THE FIRST TIME

CMP30 RAM3



- Full functioning second station
- Submersible IPX7 - 3.3 Ft for 30 minutes
- Full dot matrix display
- Programmable soft keys for easy operation
- Supplied with 23 Ft of routing cable
- External audio speaker connection

240SW




- 5x8" Rectangular 4 Ohm 40 Watt PA/Hailing horn
- Compatible with GX2000 / GX2150 / GX5500S and VLH-3000

220SW



- 5" Round 4 Ohm 30 Watt PA/Hailing horn
- Compatible with GX2000 / GX2150 / GX5500S and VLH-3000

MEK-4



- Microphone extension kit
- Remote mic up to 20 Ft
- Compatible with GX5500S

MLS-300



- External loud speaker
- Available in black or white
- Bracket or flush mount
- 5 Inch diameter
- 4 Ohms

MLS-310



- 10 watt amplified speaker
- Available in black or white
- Bracket or flush mount
- 5 Inch diameter
- ON/OFF Volume control
- 8 Ohms

MLS-300i



- Intercom speaker used with VLH-3000
- PTA (push to alert) button
- Available in black or white
- Bracket or flush mount
- 5 Inch diameter
- 4 Ohms

BTK-2

Industry 1st



Bluetooth

- Wireless Bluetooth® headset
- Noise canceling boom mic
- Compatible with GX5500S
- PTT or VOX operation
- Volume and power buttons

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by VAESU MUSSEN Co., Ltd. is under license. Other trademarks and trade names are those of their respective owners.

## FIXED MOUNT VHF ACCESSORIES


MODEL	Description	QUANTUM GX5500S	MATRIX AIS+ GX2150	MATRIX GX2000	EXPLORER GPS GX1700	EXPLORER GX1600	ECLIPSE DSC + GX1200	VLH-3000
BTK-2	Bluetooth® wireless headset kit	○						
CMP30B	Remote station microphone (Black)	○	○	○	○	○		
CMP30W	Remote station microphone (White)	○	○	○	○	○		
CT-100A	23-foot extension cable for CMP30/VH-310	○	○	○	○	○		
Q7000619A	External GPS antenna with 30Ft of cable	○	○	○	○	○	○	
CVS2500A	Voice scrambler	○	○	○				
HC1100	Dust Cover						○	
HC1600	Dust Cover				○	○		
HC2000	Dust Cover		○	○				
MEK-4	Microphone Extension Kit (20')	○						
MLS-300	External speaker	○	○	○	○	○	○	○
MLS-300i	Intercom speaker with push-to-alert							○
MLS-310	External speaker with 10 W amplifier	○	○	○	○	○	○	○
MMB-84	Flush mount bracket	○	○	○			○	○
MMB-97	Flush mount bracket				○	○		
VH-310	Remote telephone style handset	○						
220SW	5" Round 4 Ohm 30 Watt PA/hailing horn	○	○	○				○
240SW	5 x 8" Rectangular 4 Ohm 40Watt PA/hailing horn	○	○	○				○



# FIXED MOUNT SPECIFICATIONS

UNPARALLELED PERFORMANCE AT EVERY LEVEL

	<b>GX5500S</b>	<b>GX2150/GX2000</b>
		
<b>GENERAL</b>		
Input Voltage	13.8 VDC $\pm 20\%$	13.8 VDC $\pm 20\%$
Current Drain	Standby: 0.5 A	Standby: 0.55 A
	Receiver: 1.5 A	Receiver: 0.8 - 0.9 A
	Transmit: 5.0 A (Hi), 1.5 A (Lo)	Transmit: 5.0 A (Hi), 1.0 A (Lo)
Overall Dimensions	3.5"H x 9.1"W x 5.9"D (90H x 230W x 150D mm)	3.1"H x 7.1"W x 6.3"D (80H x 180W x 160D mm)
Flush-Mount Dimensions	2.8"H x 8.1"W x 5.1"D (72H x 205W x 130D mm)	2.6"H x 6.3"W x 5.9"D (65H x 161W x 150D mm)
Weight	3.2 lbs (1.5 kg)	3.1 / 3.2 lbs (1.5 kg)
PA/FOG Power Output	30 W with listen back	30 W with listen back / 30 W no listen back
<b>TRANSMITTER</b>		
RF Output	25 W (Hi), 1 W (Lo)	25 W (Hi), 1 W (Lo)
Conducted Spurious Emissions	80 dB (Hi), 66 dB (Lo)	Less than 80 dBc (Hi), 66 dBc (Lo)
Frequency Stability	$\pm 6$ ppm -4° F to +140° F	$\pm 3$ ppm -4° F to +140° F
FM Hum and Noise	50 dB	50 dB
<b>RECEIVER (for Voice and DSC)</b>		
Sensitivity (12 dB SINAD)	0.30 $\mu$ V	0.30 $\mu$ V
Spurious and Image Rejection	80 dB	80 dB for Voice (75 dB for DSC)
Intermodulation and Rejection	80 dB	80 dB for Voice (75 dB for DSC)
Audio Output	4.5 W	4.5 W
DSC Format	Class D, TU-R, M493-13	Class D, TU-R, M493-13
<b>RECEIVER (for AIS)</b>		
Sensitivity		0.5 $\mu$ V *2
Selectivity		Spurious and Image Rejection 70 dB *2
		Intermodulation and Rejection 70 dB *2
<b>NMEA Input/Output</b>		
NMEA-0183	Input: GLL, GGA, RMC and GNS (4800 bps)	Input: GLL, GGA, GNS, RMC, GSA *2 and GSV *2 (4800 or 38400 *2 bps)
	Output: DSC and DSE (4800 bps)	Output: DSC, DSE (4800 or 38400 *2 bps)
NMEA 0183 HS		Output: VDM *2 (38400 bps)


	<b>VLH-3000</b>
	
<b>GENERAL</b>	
Input Voltage	13.8 VDC $\pm 20\%$
PA Output	Two 30W (at 4 ohm 10 % distortion)
IC Output	Two 4W (at 4ohm 10 % distortion)
Listen-Back Input Level	2 mV
<b>AF Output</b>	
EXT SPK Output	More than 4 W (at 4 ohm 10 % distortion)
INT SPK Output	More than 2 W (at 8 ohm 10 % distortion)
Mic sensitivity	10 mV
Drawn current	8 A, MAX) when Forward and Aft Horns are used
Idle current	300mA
Operating temperature	4° F to +131° F
Storage temperature	22° F to +158° F
Water integrity performance	IPX7 (3 ft for 30 min) for the front panel
Overall Dimensions	4.3"W x 7.1"H x 5.5"D (110W x 180H x 140D mm)
Flush mount dimensions	3.6"W x 6.5"H x 4.5"D (92W x 165H x 115D mm)
Weight	3 lbs (1.4 kg)

	<b>GX1700</b>	<b>GX1600</b>	<b>GX1200</b>
			
<b>GENERAL</b>			
Input Voltage	13.8 VDC $\pm 20\%$	13.8 VDC $\pm 20\%$	13.8 VDC $\pm 20\%$
Current Drain	Standby: 0.45 A	Standby: 0.45 A	Standby: 0.3 A
	Receive: 0.8 A	Receive: 0.8 A	Receive: 1.0 A
	Transmit: 5.0 A (Hi), 1.0 A (Lo)	Transmit: 5.0 A (Hi), 1.0 A (Lo)	Transmit: 5.5 A (Hi), 1.5 A (Lo)
Overall Dimensions	3.4"H x 5.9"W x 3.5"D (85H x 150W x 90D mm)	3.3"H x 5.9"W x 3.5"D (85H x 150W x 90D mm)	2.4"H x 6.1"W x 6.7"D (60H x 155W x 170D mm)
Flush Mount Dimensions	2.8"H x 5.4"W x 2.6"D (72H x 137W x 65D mm)	2.8"H x 5.4"W x 3.5"D (72H x 137W x 90D mm)	2.0"H x 5.2"W x 5.5"D (51 x 131 x 140 mm)
Weight	2.0 lbs (0.9 kg)	2.0 lbs (0.9 kg)	2.0 lbs (920 g)
PA/FOG Power Output			
<b>TRANSMITTER</b>			
RF Output	25 W (Hi), 1 W (Lo)	25 W (Hi), 1 W (Lo)	25 W (Hi), 1 W (Lo)
Conducted Spurious Emissions	Less than 80 dBc (Hi), 66 dBc (Lo)	Less than 80 dBc (Hi), 66 dBc (Lo)	80 dB (Hi), 66 dB (Lo)
Frequency Stability	$\pm 3$ ppm -4° F to +140° F	$\pm 3$ ppm -4° F to +140° F	$\pm 3$ ppm -4° F to +122° F
FM Hum and Noise	50 dB	50 dB	50 dB
<b>RECEIVER (for Voice and DSC)</b>			
Sensitivity (12dB SINAD)	0.25 $\mu$ V	0.25 $\mu$ V	0.25 $\mu$ V
Spurious and Image Rejection	80 dB for Voice (75 dB for DSC)	80 dB for Voice (75 dB for DSC)	75 dB
Intermodulation and Rejection	70 dB for Voice (70 dB for DSC)	70 dB for Voice (70 dB for DSC)	70 dB
Audio Output	4.5W	4.5W	4.5W
DSC Format	Class D ITU-R M493-13	Class D ITU-R M493-13	Class D TL-R M493-13
<b>NMEA Input/Output</b>			
NMEA 0183 (4800bps for Position Data)	Input: GSA, GSV, GGA, GLL, GNS and RMC	Input: GSA, GSV, GGA, GLL, GNS and RMC	Input: GLL, GGA, RMC and GNS
	Output: DSC and DSE	Output: DSC and DSE	Output: DSC and DSE
NMEA 0183 HS (38400bps for AIS Data)			
<b>GX1700 GPS Specifications</b>			
Channels	12 channels		
Sensitivity	Less than -130 dBm		
Time to First Fix	1 min typical (@Cold Start)		
	40 sec typical (@Warm Start)		
Geodetic Datum	WGS84		
SBAS Correction	WAAS, MSAS and EGNOS		

Standard Horizon reserves the right to make changes and improvements to this product without notice. Current specifications are therefore subject to change without notice.



# TOUCH SCREEN MULTIMEDIA CHARTPLOTTERS




## CPN700i



## CPN700i




- 10.4" x 6.5" high resolution wide screen touch screen display
- VGA 1024 x 600 high resolution wide screen touch screen display
- Works with auxiliary output to connect to your onboard stereo
- Ability to use option keyboard and mouse
- Web Browser and Media Player built-in
- Memory stick to watch movies, view pictures, or listen to music
- 3D Cartography for viewing 3D, raster or vector charts
- WAAS GPS antenna with external antenna connection
- AIS and Radar capable
- Model (2) Video Inputs and Picture-in-Picture display
- Video output
- Compatible
- With independent
- Boarder Alarm
- Mounting bracket and flush mounting hardware




### Internet & Multimedia at your finger tips

With built-in Wi-Fi you can access the Internet from any web browser, email or even reply with an onscreen touch sensitive keyboard. If you prefer, connect mouse and keyboard via the easily accessible USB port. For onboard entertainment the CPN Series has been designed with built-in speakers. Simply connect a USB memory drive to watch movies, view pictures, or listen to music. For improved audio quality take advantage of the built-in stereo amplifier and connect to your onboard stereo speakers.





### GPS Status page




### Highway page



**C-MAP 4D** – Customize the way you cruise, sail or fish today ... and tomorrow. C-MAP 4D is the only maritime chartplotting solution that lets you completely customize your digital navigation charts. You choose the content (MAX or 4D), and you choose when to purchase additional Value-Added-Data to enhance your boating or sailing experience.



### 2D/3D Raster Overlay



### 2D/3D Satellite Overlay



# GPS CHARTPLOTTERS



## CP590



## CP390i




## CP190i



### Features:

- CP190i: 5 inch 320x240 resolution display
- CP390i: 7 inch 800x480 high resolution wide screen display
- CP590: 12 inch 800x600 high resolution display
- Internal 50 channel GPS receiver with external GPS connection
- Supplied with external 50 channel WAAS GPS antenna (CP590)
- Video input with Picture In Picture display (CP390i 1 input, CP590 2 inputs)
- VGA video output connects to an external monitor or compatible TV (CP590)
- C-MAP NT+ and C-MAP MAX cartography options
- AIS, Fish Finder and Radar capable
- Displays DSC Distress and Position report calls received from a DSC VHF radio
- Dual chart window with independent zoom levels
- Route Checking and Guardian Alarm
- Supplied with a swivel bracket and flush mounting hardware

### BUILT-IN CHARTS



# GPS CHARTPLOTTER / FISH FINDER COMBOS



## CPF390i



## CPF190i



### Features:

- CPF190i: 5 inch 320x240 resolution display
- CPF390i: 7 inch 800x480 high resolution wide screen display
- Internal 50 channel WAAS GPS receiver and antenna
- External 50 Channel WAAS GPS Smart antenna option
- Video input with Picture In Picture display (CPF390i 1 input)
- C-MAP NT+ and C-MAP MAX cartography options
- AIS, Fish Finder and Radar capable
- Dual chart window with independent zoom levels
- Route Checking and Guardian Alarm
- Supplied with a swivel bracket and flush mounting hardware



### Fish Finder Features

- Built-in 600 W Dual frequency Fish finder
- 50 and 200 kHz dual frequency selection
- Bottom Lock and White Line selections
- Sensitivity Time Control (STC) and Surface Noise Filter
- Speed through water (if available on transducer)
- Alarms - Shallow, Depth, Temp Upper and Lower



### BUILT-IN CHARTS

Built-in detailed maps for coastal navigation of USA including Alaska, Hawaii and Great Lakes, Canada, Bahamas, Caribbean, Cuba, Mexico, Puerto Rico, and Central America



### C-Map Max Optional Cartography

Bring your electronic charts to life with the ultimate navigator. You'll benefit from the most accurate chart detail, versatile features and a wealth of useful data.



# GPS CHARTPLOTTER VHF ACCESSORIES

## GPS CHART PLOTTER ACCESSORIES

MODEL	Description	CPN1010i	CPN700i	CP590	CP390i	CP190i	CPF390i	CPF190i
ACAC10	Line Out Audio Adapter Cable	○	○					
ACVC10	Video Adapter Cable	○	○	○	○		○	
DST520A	600 W 2" Nylon Thru-Hull Depth/Temp	*	*	*	*	*	○	○
DST521	600 W Transom Mount Depth/Speed/Temp	*	*	*	*	*	○	○
DST523	600 W 2" Bronze Thru Hull Depth/Temp	*	*	*	*	*	○	○
DST525	600 W In-Hull Depth Transducer	*	*	*	*	*	○	○
DST526	600 W Bronze Thru Hull Depth/Speed/Temp with fairing block	*	*	*	*	*	○	○
DST527	1000 W In-Hull Depth Transducer	*	*	*	*	*		
DST528A	1000 W Thru-Hull Depth/Temp with fairing block	*	*	*	*	*		
FF525	Dual Frequency Black Box Fish Finder Module	○	○	○	○	○		
VGAC10	VGA Adapter Cable	○		○				
Q7000619A	50 Channel GPS NMEA Antenna with 30 Feet of routing cable	○	○	○	Option	Option	Option	Option

\*Can be used when FF525 is connected

## FISHFINDER AND TRANSDUCERS



**FF525 Black box fishfinder**  
 • 50/200 kHz Dual frequency  
 • 600 W or 1000 W output

Power supply : 10 - 35 VDC  
 Max stand by current draw : 1000 W:142 mA at 12 VDC  
                                       : 600 W:100 mA at 12 VDC  
 Max current draw 1000W : 1.42A at 12 Volt DC  
                                       : 600 W:1A at 12 Volt DC  
 Power Output : 600/1000 W (4800/8000 WPeak to Peak)  
 Display Colors : 256 and 16 color capable  
 Display/Vertical Resolution : 400 pixels on CP390i, CP590, CPV550, CPN700i and CPN1010i  
                                       : 200 pixels on CP190i  
 Frequency : Dual 50 and 200 kHz  
 Max Depth\* : 1000 W:1200 Ft (365 m) at 200 kHz; 4000 Ft (1219 m) at 50 kHz  
                                       : 600 W:700 Ft (213 m) at 200 kHz; 1500 Ft (457 m) at 50 kHz

Min Depth : 2.5 Ft (0.8 m) at 200 kHz; 5 Ft (1.6 m) at 50 kHz  
 Max Typical\* : 1000 W:980 Ft (299 m) at 200 kHz; 2700 Ft (823 m) at 50 kHz  
                                       : 600 W:600 Ft (183 m) at 200 kHz; 1350 Ft (411 m) at 50 kHz  
 NMEA output sentences : Depth: DBT, DPT  
                                       Temperature: MTW  
                                       Speed (with DST521 or DST526): VHW  
 Weight : 2.20 LBS (1 kg)  
 Operating temperature range : 32° F to 122° F (0° C to +50° C)  
 Storage temperature range : -4° F to 158° F (-20° C to +70° C)  
 Dimensions : 7.73" W x 1.96" H x 6.5" D (196.4W x 50H x 164.96D mm)

**NOTE\*** This is not a guaranteed specification. The actual maximum depth capability of the system depends on the type of transducer fitted, the reflectivity of the bottom, water condition, etc.

### 600 W TRANSDUCERS



**DST520**  
 2" Nylon Thru-Hull  
 Depth & Temp



**DST521**  
 Transom Mount,  
 Depth, Speed & Temp



**DST523**  
 2" Bronze Thru-Hull  
 Depth & Temp



**DST525**  
 In-Hull Mount,  
 Depth



**DST526**  
 Bronze Thru-Hull, Triducer,  
 Depth, Speed & Temp,  
 with fairing block




**DST527**  
 In-Hull Mount,  
 Depth



**DST528A**  
 Thru-Hull, Long stem,  
 Depth & Temp  
 with fairing block

### ■ Conceptual diagram of location and connection



**NOTE:** The GX1600 and GX1700 Explorer and the GX2000 and GX2150 Matrix Fixed Mount VHF radios can connect to one optional remote microphone and the GX5500S can connect up to two optional remote microphones.





**Q7000619A**  
 External GPS Antenna  
 50 Channel GPS NMEA Antenna  
 with 30 feet of routing cable



# GPS CHARTPLOTTERS SPECIFICATIONS

UNPARALLELED PERFORMANCE AT EVERY LEVEL

## Touch screen and Multimedia ChartPlotters

	CPN1010i	CPN700i
		
<b>GENERAL</b>		
Input Voltage	10-35 VDC	10-35 VDC
Current Drain	1.5 A	750 mA
Display	10.1" bonded touch screen Sunlight viewable technology	7" bonded touch screen Sunlight viewable technology
Display Resolution	WSVGA 1024 x 600	WVGA 800 x 480
Aspect Ratio	16 x 9	16 x 9
Brightness	1000 nits	1000 nits
Contrast	500:1 contrast	250:1 contrast
Cartography	built-in, optional C-Map 4D	built-in, optional C-Map 4D
Operating Temperature Range	32° F to +131° F (0° C to +55° C)	32° F to +131° F (0° C to +55° C)
Overall Dimensions	7.5"H x 12"W x 2.8"D	5.9"H x 9.3"W x 2.8"D
Flush Mount Dimensions	6.8"H x 10.6"W	5.5"H x 8"W
Weight (without bracket)	4.4 lbs	2.7 lbs
User Points	Marks/waypoints 3000 Routes 50/100 points each	Marks/waypoints 3000 Routes 50/100 points each
Track Points	10,000	10,000
NMEA 0183 Out/In	RS232: 3/2, RS422: 2/2	RS232: 3/2, RS422: 2/2
Internal GPS Type	WAAS, 50 channel	WAAS, 50 channel
Bluetooth®	Bluetooth® version 2.1	Bluetooth® version 2.1
WiFi	802.11b/g/n	802.11b/g/n
USB	On rear panel	On rear panel
Low Level Audio Output	100 mV to 4 V	100 mV to 4 V
Video	2 Video input NTSC/PAL with Picture in Picture / VGA output	1 Video input NTSC/PAL with Picture in Picture

	CP590	CP390i	CP190i	CPF390i	CPF190i
					
<b>GENERAL</b>					
Input Voltage	10-35 VDC	10-35 VDC	10-35 VDC	10-35 VDC	10-35 VDC
Current Drain	1.5 A max	750 mA max	520 mA max	2.3 A max	2.2 A max
Display	TFT Color LCD (Active area 12") Sunlight viewable 256-color	TFT Color LCD (Active area 7") Sunlight viewable 256-color	TFT Color LCD (Active area 5") Sunlight viewable 256-color	TFT Color LCD (Active area 7") Sun viewable 256-Color	TFT Color LCD (Active area 5") Sun viewable 256-Color
Display Resolution	800 x 600 pixels	800 x 480 pixels	320 x 240 pixels	800 x 480 pixels	320 x 240 pixels
Cartography	C-MAP NT+ / MAX C-Card	C-MAP NT+ / MAX C-Card	C-MAP NT+ / MAX C-Card	C-MAP NT+ / MAX C-Card	C-MAP NT+ / MAX C-Card
Operating Temperature Range	32° F to +131° F (0° C to +55° C)	32° F to +131° F (0° C to +55° C)	32° F to +131° F (0° C to +55° C)	32° F to +131° F (0° C to +55° C)	32° F to +131° F (0° C to +55° C)
Overall Dimensions	10.2"H x 15.4"W x 6.3"D	5.7"H x 9.9"W x 1.5"D	4.4"H x 7.1"W x 1.7"D	5.7"H x 9.9"W x 2.5"D	4.3"H x 7.1"W x 2.3"D
Flush Mount Dimensions	8"H x 10.8"W	4.3"H x 9"W	3.4"H x 6.5"W	4.25"H x 9"W	3.75"H x 6.5"W
Weight (without bracket)	6.6 lbs (3 kg)	2 lbs (920 g)	1.3 lbs (600 g)	2.5 lbs (1120 g)	1.7 lbs (780 g)
User Points	Marks/Waypoints 3000 Routes: 50 (max 100 Waypoints each)	Marks/Waypoints 3000 Routes: 50 (max 100 Waypoints each)	Marks/Waypoints 3000 Routes: 50 (max 100 Waypoints each)	Marks/Waypoints 3000 Routes: 50 (max 100 waypoints each)	Marks/Waypoints 3000 Routes: 50 (max 100 waypoints each)
Track Points	10,000 (recordable in 20 tracks)	10,000 (recordable in 20 tracks)	10,000 (recordable in 20 tracks)	10,000 (recordable in 20 tracks)	10,000 (recordable in 20 tracks)
NMEA 0183	5 Outputs and 4 Inputs	5 Outputs and 4 Inputs	3 Outputs and 2 Inputs	3 Outputs and 3 Inputs	2 Outputs and 1 Input
Receiver Type	WAAS, 50 Channel	WAAS, 50 Channel	WAAS, 50 Channel	WAAS, 50 Channel	WAAS, 50 Channel
Fish Finder Power Out				600W	600W
Dual Frequency				50 and 200 kHz	50 and 200 kHz
Depth Capability				2.5 Ft to 700 Ft at 200 kHz 5 Ft to 1500 Ft at 50 kHz	2.5 Ft to 700 Ft at 200 kHz 5 Ft to 1500 Ft at 50 kHz



Because Standard Horizon Chart Plotters are built better, they're backed better. If your Standard Horizon Chart Plotter ever fails for any reason including water damage during normal use in the first three years, STANDARD HORIZON will repair or replace it free, without hassle or charges... period! If it fails thereafter in normal use for the life time of the product it is covered by Standard Horizon's Lifetime Flat Rate Service and Customer Loyalty Programs.

Standard Horizon reserves the right to make changes and enhancements to products at our discretion. Current specifications are therefore subject to change without notice.





## ***STANDARD HORIZON***

### **YAESU USA**

6125 Phyllis Drive, Cypress, CA 90630

Phone: (800)767-2450

Fax: (800)552-6813

**WWW.STANDARDHORIZON.COM**

2012. 1216 SS(U) B9200649 Printed in Japan



"Standard Horizon makes every effort to keep our oceans blue.  
This catalog was produced with the environment in mind please recycle."

